




PRODUCT RANGE

D

PRODUKTPROGRAMM

E

PRODUCT RANGE

	Cyl.	 mm	cm ³		Comp. Ratio ε	kW	PS	Pos
1104D-44TA Euro 3	D (LA) 4	105 x 127	4400	2	16,2:1	74-83	100-111	1
1104D-E44TA Euro 3	D (LA) 4	105 x 127	4400	2	16,2:1	75-106	102-144	2

B

		Pos			Pos
B					
T SERIE					
T 2256	1104D-44TA	D			1
T 2566	1104D-44TA	D			1
T 35100	1104D-44TA	D			1
T 35100 L	1104D-44TA	D			1
T 35100 SL	1104D-44TA	D			1
T 35120	1104D-44TA	D			1
T 35120 L	1104D-44TA	D			1
T 35120 SL	1104D-44TA	D			1
T 3571	1104D-44TA	D			1
T 3571 L	1104D-44TA	D			1
T 40140	1104D-44TA	D			1
T 40170	1104D-44TA	D			1
TL SERIE					
TL 360	1104D-44TA	D			1
TL 470	1104D-44TA	D			1
TL 470 HF	1104D-E44TA	D			2

B

1 **105**
1104D-44TA Euro 3 D LA 4 4400 cm³ 2V 74-83 kW 100-111 PS ξ 16,2:1 127
T SERIE, TL SERIE

	40 529 600	Cylinder diameter: 105; KH: 70.116; MT: -22.94; M \varnothing : 50; GL: 108.05; piston pin: 39.7x78; number of piston rings: 3 RTK, TPL
		T15 3 CK G6 M 2.5 DSF 3 CR

	79 249 600	[Pair] AS STD \varnothing 87.120 / 103.850 // 2.310 St/A
	37 117 610	[Set] PL 0,254 \varnothing 63.241 / 67.208 / 31.880 / 1.969 St/A 37 117 620 0,508 / 37 117 600 STD, ohne Fixiernocken / without locating lugs / sin clavija de fijaciòn / sans ergots de fixation / без фиксирующего кулачка
	37 145 620	[Set] HL 0,508 \varnothing 75.667 / 80.416 / 31.880 / 2.343 St/A 37 145 600 STD
	105-35625	EX; 41.6 x 9 x 129.2 x A/S - Cr - 30° - 9 -
	105-35624	IN; 46.3 x 9 x 129.2 x S - Ni - 30° - 9 -
		RK-9H valve cotter; number of notches: 1; valve stem diameter: 9

2 **105**
1104D-E44TA Euro 3 D LA 4 4400 cm³ 2V 75-106 kW 102-144 PS ξ 16,2:1 127
TL SERIE

	40 040 600	Cylinder diameter: 105; KH: 70.116; MT: -15.7; M \varnothing : 76.6; GL: 108.05; piston pin: 39.7x86; number of piston rings: 3 RTK, TPL
		T15 3 CK G6 M 2.5 DSF 3 CR

	79 249 600	[Pair] AS STD \varnothing 87.120 / 103.850 // 2.310 St/A
	37 117 610	[Set] PL 0,254 \varnothing 63.241 / 67.208 / 31.880 / 1.969 St/A 37 117 620 0,508 / 37 117 600 STD, ohne Fixiernocken / without locating lugs / sin clavija de fijaciòn / sans ergots de fixation / без фиксирующего кулачка
	37 145 620	[Set] HL 0,508 \varnothing 75.667 / 80.416 / 31.880 / 2.343 St/A 37 145 600 STD
	105-35625	EX; 41.6 x 9 x 129.2 x A/S - Cr - 30° - 9 -
	105-35624	IN; 46.3 x 9 x 129.2 x S - Ni - 30° - 9 -
		RK-9H valve cotter; number of notches: 1; valve stem diameter: 9

COMPARISON LIST

D

VERGLEICHSLISTE

E

COMPARISON LIST
