

Safety first – for every bolt

NEW



www.elring.de

Elring-Service-Hotline

 +49 7123 724-799

 +49 7123 724-798

service@elring.de



EL 2012 B EL 2012 G



Das Original

Elring threadlocking adhesive: securing bolts for maximum safety

Securing bolts and threaded assemblies to prevent loosening is an essential component of today's health and safety requirements in the field of engineering. Elring threadlockers EL 2012 B and EL 2012 G are the perfect choice – for professional and effortless handling.

- Secure and seal threaded assemblies.
- Convenient 10 ml bottle for effective application.
- Excellent temperature resistance and substance tolerance.
- Meets strict health and safety standards; no labeling required under CLP regulations (hazard pictograms, hazard/safety notices), as the product contains no dangerous substances.
- Modern Elring packaging design, attractively presented in a matching POS display.

Whether passenger car, commercial vehicle, motorcycle or vintage car, or even motor racing and water sports: Elring provides the ultimate seal. When it comes to operational safety and reliability, you can rest assured that Elring will deliver the very best performance. Elring offers an extensive range of products for professional component sealing – used millions of times around the globe. You can count on it.

Technical Data

	EL 2012 B (700.500)	EL 2012 G (700.520)
Type of product	Anaerobic threadlocking adhesive	Anaerobic threadlocking adhesive
Strength	Medium	High
Color	Blue	Green
Temperature range	-55 °C to +150 °C	-55 °C to +150 °C
Maximum bond gap capacity	0.25 mm	0.15 mm
Maximum thread size	M36	M20
Resistance to	Oil, lubricant, fuel, coolant, cold and hot water, salt water, etc.	Oil, lubricant, fuel, coolant, cold and hot water, salt water, etc.
Minimum shelf life	24 months	24 months
Bottle size	10 ml	10 ml

